


NO SCALE

NOTES:

1. BALES SHALL BE PLACED WITH ENDS TIGHTLY ABUTTING THE ADJACENT BALES.
2. EACH BALE SHALL BE EMBEDDED IN THE SOIL A MINIMUM OF 4" AND PLACED SO THAT BINDINGS ARE HORIZONTAL.
- 3 BALES SHALL BE SECURELY ANCHORED IN PLACE BY EITHER TWO STAKES OR TWO RE-BARS DRIVEN THROUGH THE BALE. THE FIRST STAKE IN EACH BALE SHALL BE DRIVEN TOWARD THE PREVIOUSLY LAID BALE AT AN ANGLE TO FORCE THE BALES TOGETHER. STAKES SHALL BE DRIVEN FLUSH WITH THE BALE.
4. INSPECTION SHALL BE FREQUENT AND REPAIR OR REPLACEMENT SHALL BE MADE PROMPTLY AS NEEDED.
5. BALES SHALL BE REMOVED WHEN THEY HAVE SERVED THEIR USEFULNESS SO AS NOT TO BLOCK OR IMPEDE STORM OR DRAINAGE.



CITY OF OAK FOREST
STANDARD DETAIL
FOR
STRAW BALES AROUND
DRAIN AREA
 DATE: MAR 2019
 SOIL EROSION\STRAWBALE2